

2000 Series



DeMARCO® INDUSTRIAL VACUUMS

The Portable **DeMARCO**® **Vacuum 2000 Series** is precisely engineered and manufactured to the highest standards, therefore providing you with a level of unsurpassed quality, value and performance.

The 2000 Series is ideal for medium to heavy-duty wet/dry material applications that may require up to a 5" ID hose size with pick up capacities up to 14 tons/hour. This compact design is easily maneuverable with an included hydraulic hand-lift truck. The Portable 2000 Series may also be connected to a central manifold system with multiple pick up point connections.

YOUR SEARCH STOPS HERE™

DeMARCO® Vacuums are purposely built for decades of heavy-duty use with our exclusive performance features that are virtually maintenance-free. From our heavy gauge steel fabrications, to our time tested quality components and expert machine craftsmen, we are confident to stand behind every vacuum system that carries the DeMARCO® name worldwide by offering our exclusive **Limited LIFETIME Warranty - Nothing Less.**

INDUSTRIES SERVED

| FOUNDRY FOOD | <u>Mills</u> | <u>Mining</u> | PLASTIC | Power Plant | Misc. |
|--|---|---|------------------------------|---------------------------|-------------------------------------|
| ALUMINUM FLOUR BRONZE GRAIN CARBON BLACK SALT METAL SUGAR ORES SAND CLAYS STEEL SHOT | CHEMICALS SAWDUST PAPER PULP WOOD CHIPS | ASPHALT BRICK CEMENT CONCRETE GRAVEL LIMESTONE MINERALS | FLAKES POWDER PELLETS RESINS | Coal Fly Ash Slurry | COATING GLASS SODA ASH POWDERS ETC. |

PERFORMANCE

| Model | НР | Vacuum ("Hg) Rating* | CFM | Inlet ID Hose Size | Tons/ Hour** |
|-------|----|-------------------------|------|-----------------------|-----------------|
| 2250 | 25 | 16" | 660 | 3" | 5 |
| 2300 | 30 | 16" | 790 | 3-1/2" | 8 |
| 2400 | 40 | 16" | 950 | 4" | 10 |
| 2500 | 50 | 16" | 1150 | 5" | 14 |

Above performances are approximate ratings under STP.

^{*} Vacuum capabilities up to 27" Hg available on select models.

^{**} Actual values may differ based upon distance from blower and material characteristics such as bulk density, particle size and operator's efficiency.

DeMARCO® MAXCARTRIDGE™ FILTERS

2000 Series

- Exclusive Long Lasting Custom Design
- · Washable and Reusable
- · High Burst Strength with Dimensional Stability
- Dimpled, Non-Clogging Open Pleat Design
- · Handles Ultra-Fine Powders
- Abrasion and Chemical Resistant
- Efficiencies up to 99.99% @ 0.2 Microns & Above
- · Interval Air-Pulse Cleaning for Uninterrupted Vacuuming. No Manual Filter Shaking Required
- Secondary In-line or HEPA Filters Available
- · Various Filter Medias Available
- Filter Performance Guarantee
- * Minimum 80 PSI Compressed Air Required for Filter Pulse Cleaning During Vacuuming.




DIMENSIONS


| Roll Hopper in Cubic Yards | L | W | Н |
|-------------------------------|-------|-------|-------|
| 1/2 | 6'-1" | 4'-1" | 7'-5" |
| 1 | 7'-4" | 5' | 7'-2" |
| 1-1/2 | 8'-6" | 5'-5" | 9'-4" |
| 2* | 8'-5" | 6'-7" | 9'-1" |
| 2-1/2* | 8'-4" | 6'-7" | 9'-9" |


Custom dimensions available.

HEPA Filter Option may add to overall height.

^{*4-}Point powerhead air-lift package required.







FEATURES & BENEFITS

Patented Features

- DeMARCO® Material Offset Separation Circuit Provides Minimal Carryover to the Filtration Chamber Maximizing Filter Performance.
- Exclusive Line of Cyclone Separators
- DeMARCO® Silencer Base® Muffler
 - Low dBA Rating
- Compact and Esthetic Design
- Solid Support Structure for the Drive Package
- Fork Tine Openings for Vacuum Mobility

Control Panel

- NEMA 4 or 4X Enclosures
- 480V/3PH/60HZ or as Required
- Start/Stop Push-Buttons
- · Material High Level Detector with Auto Shutdown
- Differential Pressure Switch for Filter Protection
- Magnehelic and Vacuum Gauges
- Vacuum Pump High Temperature Protection Circuit
- · Engineered Electrical Drawings Included
- UL Approved
- · Options:
- NEMA 7/9 X-Proof Packages
- -12V DC Panel
- PLC Touch Screen Terminal

Drive Package

- High Performance Positive Displacement Vacuum Pumps
- Continuous 24/7 Operation
- Up to 27" Hg (Mercury) Available
- High Energy Efficient Electric Motors
- · V-Belt or Direct Drive
- · Gas, Diesel and LPG Options

Roll Hopper and Structural Stand

- 1/2, 1, 1-1/2, 2 or 2-1/2 Material Collection Roll Dump Hoppers with Safety Latch and Skid Mounting Base
- Heavy-Duty Structural Support Stand with 5500 lb. Hydraulic Hand-Lift Truck for Sealing and Movement of Hopper or Transport of Vacuum.
- Optional 4-Point Powerhead Air-Lift Package. No Manual Hand-Lift or Fork-Lift Truck Required for Hopper Sealing
- Optional Over-the-Road Trailer Mounted or In-Plant 2-Wheel/4-Wheel Tow Packages Available

Custom Engineered Vacuums

Our full service custom engineering department is dedicated to provide customer focused solutions for your toughest applications.

DeMarco Industrial Vacuum Corp PO Box 1138 Crystal Lake, IL 60039 USA

P: 815.344.2222 F: 815.344.2223 DeMarcoVacuums.com Sales@DeMarcoVacuums.com

